



91606

EAN 4043619916061



3,5" USB 2.0 Card Reader 24in1 Multipanel



Description

This card reader for the installation in a 3,5" bay of your PC offers both an internal connection to the USB-connector of the mainboard and an external connection via a provided cable with slot bracket. The package content also includes two additional front panel in black and silver whereby the installation in designer PC's does not cause a problem in terms of color. After the installation of the driver all four slots are available for pictogram (flashcard display). The use of two data storages at the same time is also possible. Additional to the card reader a USB-port is provided.

Specification

- Supports 3.3V SM / SM RAM Card / SM ROM Card / MMC / RS-MMC / MMC DualVoltage / RS-MMC Dual Voltage / MS / MS-Pro / MS Duo / MS-Pro Duo / MS Magic Gate / MS Seclet / CFI / CFII / MD / Magicstore / SD / Mini-SD / xD / MS-Duo Magic Gate / MS-Pro Magic Gate / MS-Pro Duo Magic Gate / SD adapter f. TransFlash
- USB-Port
- Status icon for the card reader
- USB bus power, no external power supply required

System requirements

- one free USB port
- Windows 95/98/98SE/ME/2000/XP, Vista, Mac OS 8.6 or later, Linux OS 2.4.X or higher

Package content

- card reader with connectingcabel to mainboard
- additional cable for external connection to USB port
- 1 x silver, 1 x black frontpanel, 4 screws for montage
- driver CD with user manual

Package

- Retail Box